

ULTRA Side Pocket Anchor Selection Table

RECOMMENDED ULTRA SIDE POCKET ANCHOR WEIGHT	SAIL BOAT			POWER BOAT			MULTIHULL		
	 MONO HULL			  HIGH PROFILE LOW PROFILE			  SAIL POWER		
	Boat Weight		Boat Length	Boat Weight		Boat Length	Boat Weight		Boat Length
	(kg) / (lbs)	(ton) (lbs)	(m) (feet)	(ton) (lbs)	(m) (feet)	(m) (feet)	(ton) (lbs)	(m) (feet)	(m) (feet)
	21/46	3,8 - 8 380	9 - 30	4,2 - 9 260	9,3 - 31	10,2 - 33	2,7 - 5 950	7,8 - 26	8,2 - 27
27/60	6,3 - 13 890	10,8 - 35	6,9 - 15 210	11,1 - 36	12,2 - 40	4,5 - 9 920	9,3 - 31	9,8 - 32	
35/77	10,2 - 22 490	12,6 - 41	11,2 - 24 690	13 - 43	14,3 - 47	7,3 - 16 100	10,9 - 36	11,5 - 38	
45/100	14,6 - 32 190	14,3 - 47	16 - 35 270	14,7 - 48	16,2 - 53	10,5 - 23 150	12,4 - 41	13 - 43	
60/132	21,5 - 47 400	16 - 52	23,5 - 51 800	16,5 - 54	18,2 - 60	15,6 - 34 400	13,8 - 45	14,6 - 48	
80/176	30 - 66 140	17,8 - 58	32,9 - 72 530	18,3 - 60	20,1 - 66	21,6 - 47 620	15,4 - 51	16,2 - 53	
100/220	43 - 94 800	20 - 66	47,1 - 103 830	20,6 - 68	22,7 - 74	31 - 68 340	17,3 - 58	18,2 - 60	
130/290	63 - 139 880	22,3 - 73	69 - 152 120	23 - 75	25,3 - 83	45,4 - 100 100	19,3 - 63	20,3 - 67	
160/350	85 - 187 000	24,5 - 80	93 - 205 000	25,2 - 83	27,7 - 91	61 - 134 000	21,2 - 70	22,3 - 73	
200/440	123 - 271 000	27,4 - 90	135 - 298 000	28,2 - 93	31 - 102	89 - 196 000	23,7 - 78	25 - 82	
250/550	174 - 384 000	30,4 - 100	191 - 421 000	31,3 - 103	34,4 - 113	125 - 276 000	26,3 - 86	27,7 - 91	
300/660	262 - 578 000	34,4 - 113	287 - 630 000	35,4 - 116	39 - 128	190 - 419 000	29,8 - 98	31,3 - 103	
360/800	400 - 882 000	39,2 - 129	438 - 966 000	40,4 - 133	44,4 - 146	290 - 639 000	33,9 - 111	35,7 - 117	
420/925	550 - 1 213 000	44 - 144	600 - 1 323 000	45,3 - 149	49,8 - 163	400 - 882 000	38,1 - 125	40 - 131	
500/1100	760 - 1 675 000	50 - 164	830 - 1 830 000	51,5 - 169	56,7 - 186	550 - 1 213 000	43,3 - 142	45,5 - 150	

COMMENTS:

- When Selecting ULTRA Anchors in excess of 500Kg/1100lbs, please consult Lloyd's or a comparable certification society's guidelines. The listed values should be used for preliminary selection only.

- If used in a side pocket setup, the anchor must be "Balanced".

- If used in a bow setup, the anchor should be "Unbalanced".

- This table applies to all Ultra Side Pocket Anchors, both Standard and Compact.

WARRANTY:

- Properly selected ULTRA Side Pocket Anchors are covered by our lifetime warranty against issues arising from production or normal use.

CAUTION:

- The ULTRA Side Pocket Anchor is designed to handle extreme heavy loads and caution is advised when handling.

- All materials have resistance limits. The use of high powered engines to free an anchor may deform it and/or cause damage to the vessel.

- It is recommended to use a trip line to recover an anchor stuck under an obstruction.



ULTRAProducts
WEST

We reserve the right to make changes to dimensions and conditions.

This document was updated on the 14.03.2025

For the latest version, please visit www.ultraproductswest.com